
Turbosheet 2mm

1. PRODUCT DESCRIPTION

Turbo-Sheet is a SBS (Styrene-Butadiene-Styrene) sheet which has a thickness of 2.0mm, width of 1m and length 20m per roll.

2. USAGE

Turbosheet is used as a protection layer to be applied in conjunction with Turboseal P. It can be used for all types of concrete structures including typical buildings, roofs, utility tunnels, electric cable tunnels, underground structures, power plants, and sewage treatment plants etc.

3. APPLICATION

- (1) Surfaces shall be cleaned and free of foreign materials and shall be completely dried.
- (2) Apply Turboseal P.
- (3) Install Turbosheet by embedding it into Turboseal P.

5. PHYSICAL PROPERTIES

Test Item	Unit	Quality Standard	Test Method
Tensile Strength	N/mm	More than 5.0	KS F 4917
Elongation	%	More than 15	
Tear Strength	N	More than 20	

6. PACKAGING

Turbosheet is manufactured in 1 m (width) x 20m (length) rolls.

7. Handling and Storage

- must be used in order of its arrival at site
- must be stored in a well-ventilated area
- avoid contact with water
- If stored outside (during application), place it on a plywood/wooden pallet and cover it with waterproofing / PE film to protect it from rain, dew formation and UV exposure etc.

8. Expiration date

Up to two years depending on the storage and handling conditions.

Contact Us:

All Aspects Insulation Materials
P.O.Box: 39613, Sharjah
United Arab Emirates
Tel: +971 6 5569913
Fax: +971 6 5569914
E: info@allaspects-emirates.com
W: www.allaspects.ae